




J-Channel



- 
Almond
 w/almond cord
- 
Black
 w/black cord
- 
White
 w/white cord

DESCRIPTION:

J-Channels are custom-developed to attach to the front of standard retail shelving by means of the ID channel. This is accomplished with two stainless steel cams that allow for simple quarter-turn installation and removal. The J-Channel LEDs provide both up and down lighting to illuminate products above and below the unit. The front contour of the channel duplicates the existing pricing channel to insure no lost space for pricing or marketing information.

- Unique shape reflects light back toward product
- Mounts seamlessly into standard gondola merchandising shelving
- Two stainless steel cams inside channel allow for simple quarter-turn installation and removal
- Up and down lighting self-contained in one fixture
- Custom lengths available
- Four LED color temperatures available
- UL Listed
- 5 Year Warranty



SPECIFICATIONS:

LED Type	Standard	Bright
Recommended Target Distance	< 12"	12–24"
Intensity	150 lm/Foot	350 lm/Foot
LED Chip	Epistar SMD 2835	
Power/Chip	0.2 Watts	0.5 Watts
CRI	Ra > 80	
Lumen/Chip	24–26	60–65
Diodes/Foot	18	
Efficiency	105–110 lm/W	115–120 lm/W
Power	1.37W/Foot	2.93W/Foot
Connector	2.1mm x 5.5mm DC barrel Connector on 22-gauge wire	
Listing	UL E474996	
CCT	3,000/4,000/5,000/6,000K	
Beam Angle	120 degrees	
Lifetime	> 50,000 Hours	
Voltage	12V	
PCB Dimensions	0.32" x 1.97"	
Dimmable	Yes	